CONTENTS

Chapter 1. INTRODUCTION

2.1	Ge	neral Specifications·····	··2-1
2.2	Pe	rformance Specifications	2-2
2.2	2.1 2.2 2.3 2.4	Basic performance specification Input specification Limit switch(L/S) input specification Transister output specification	· 2-3 ···2-3
2.3	Na	mes of Parts and Functions	2-4
2.3 2.3 2.4		Names of Parts and Functions Function of LED Indicators DIP Switch Setting Part Input / Output Terminal Block erface with External Devices	2-6 2-7 2-8 2-10
2.5		tput Mode of Encoder ······	
2.6	FU	nction Descriptions ······	
2.0 2.0 2.0	6.1 6.2 6.3 6.4 6.5	Operation Modes Comparision Signal Output Home Signal Carry Signal Borrow Signal	2-15 2-17 2-18

Chapter 3. INSTALLATION AND WIRING

3.1	Installation·····	3-1
3.	1.1 Installation Ambience	3-1
3.2	Wiring Precautions	3-1
2 2	Wiring Example	3-2
	Wiring Example	
3.3.	1 5VDC Voltage Output Type Encoder	3-2
3.3. 3.3.	•	3-2 3-3

Chapter 4. FUNCTION BLOCK

4.1 Ins	I.I Insertion of the Function Block for Hgn Speed Counter on the GMWIN4-1			
4.2 Lo	cal Function Block4-2			
4.2.1 4.2.2 4.2.3 4.2.4	The specification of the preset value(HSC_PRE) 4-2 The specification of the comparison value (HSC_CMP) 4-3 Wrting the operating Information(HSC_WR) 4-4 Reading the value of the operating status(HSC_RD) 4-5			
4.3 Re	mote Function Block4-6			
4.3.1 4.3.2 4.3.3 4.3.4	The specification of the preset value (HSCR1PRE) 4-6 The specification of the comparison value (HSCR1CMP) 4-7 Writing the operating information (HSCR1WR) 4-8 Reading the value of the operating status(HSCR1RD) 4-9			
4.4 Er	or code on the function block ······ 4-10			
Chapter	5. GM PROGRAMMING			
Chapter	5. GM PROGRAMMING			
	5. GM PROGRAMMING Degramming Examples 5-1 Enabling the counter operation 5-2 Preset 5-3 Setting the comparison value 5-4 Setting the magnitude comparison values 5-5 Reading the current count value 5-6 Enabling the external output 5-7 Coincidence reset 5-8 Carry / Borrow reset 5-9 Enabling the home latch 5-10 Read/Write when the high speed counter module Is mounted onto the remote station 5-11			
5.1 Pr 5.1.1 5.1.2 5.1.3 5.1.4 5.1.5 5.1.6 5.1.7 5.1.8 5.1.9 5.1.10	Enabling the counter operation 5-2 Preset 5-3 Setting the comparison value 5-4 Setting the magnitude comparison values 5-5 Reading the current count value 5-6 Enabling the external output 5-7 Coincidence reset 5-8 Carry / Borrow reset 5-9 Enabling the home latch 5-10			

Chapter 6. BUFFER MEMORY AND I/O SIGNAL CONFIGURATION

6.1 Operating block diagram				
6.2 Input / Output signal configuration				
6.2.1 G3F-HSCA 6-3 6.2.2 G4F-HSCA / G6F-HSCA 6-5 6.2.3 Functions of I/O Signals 6-6				
6.3 Buffer memory configuration 6-8				
6.3.1 Buffer memory configuration 6-8 6.3.2 The contents and data configuration of buffer memory 6-9				
Chapter 7. MK PROGRAMMING				
•				
7.1 Buffer Memory Read / Write7-1				
7.1.1 Read from the Buffer Memory (GET,GETP)				
7.2 Programming Examples7-5				
7.2.1 Setting Preset Value				
7.2.2 Setting Comparison Value				
7.2.4 Reading Current Count Value 7.2.4 Reading Current Count Value 7.8				
7.2.5 Enable Output				
7.2.6 Enabling Home Latch 7-9 7.2.7 Coincidence Reset 7-10				
7.2.8 Carry / Borrow Reset				
7.3 Application Examples 7.11				
7.3.1 Program for moving the cart7-11				
7.3.2 Program for Control of the Constant Angle rotation of the Turntable7-16				
Chapter 8. TROUBLESHOOTING				
8.1 Troubleshooting ·····8-1				
8.1.1 The LED status of High Speed Counter Module 8-1				
8.1.2 The counting status High Speed Counter Module 8.1.3 The output status of High S				
8.2 Troubleshooting Procedure 8-2				
8.2.1 LED indication Is Incorrect 8.2.2				
8.2.2 Count Operations Do Not Execute 8-3 8.2.3 Counter Value Is Incorrect 8-4				
8.2.4 Output Operations Do Not Execute				
8.3 Error LED List ······8-6				

Chapter 9.	DIMENSIONS
------------	------------

9.1	Dimensions		9-1
-----	------------	--	-----